

LABdex



Air-Cooled Water Chiller LX1702ACC

Email: info@labdex.com **website:** www.labdex.com

Description

Air-Cooled Water Chiller LX1702ACC an easy to operate, safe, energy-conscious and low noise equipment designed for continuous operation. They are well equipped with stainless steel tank and water pump along with digital display. Using highly precise temperature control and high efficiency compressor, they provide stable and efficient performance.

Specifications

Water tank capacity	30 L
Temperature range	5 - 25°C
Total power	3.28 kW
Cooling capacity	7.5 kW 6459 Kcal/h
Cooling fan	0.27 kW
Air volume	4000 m³/h
Evaporator	Tank + Copper Coils
Condenser	Efficient brass sets corrugated aluminum fin
Compressor	Hermetic Scroll Type or Piston 2.2 kW
Refrigerant	R407C
Power supply	3 Phase / 380 V / 50 Hz
Pump	0.75 kW
Dimension	1160 x 600 x 1220 mm

Weight	235 Kg
---------------	--------

Features

- ✓ Temperature range: 5°C to 25°C
- ✓ Energy-conscious
- ✓ Overloaded protection from current and pressure protection
- ✓ Digital display showing water temperature
- ✓ Refrigerant type of R407C
- ✓ Compressor type: Hermetic scroll type/piston
- ✓ Tank-type evaporator with copper coils and G1 inlet and outlet ports
- ✓ Stainless steel tank and water pump

Applications

- ✓ Water chiller are used in basically laboratory, food industry, biotechnology, packaging, laser etc.



71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.

Email: info@labdex.com | Website: www.labdex.com